



HDS 6/12 C

Compact hot water high pressure cleaner with eco!efficiency mode and steam function



1 Efficiency

- eco!efficiency mode – economical and environmentally friendly, even during longer periods of use.
- Reduces fuel consumption and CO2 emissions by 20%.

2 Ease of use

- Intuitive operation with large single-button selector switch.
- Large tank opening with filling chute.

3 Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose.

4 Mobility

- Jogger principle with large wheels and steering roller.
- Large integrated handles in the chassis.



HDS 6/12 C

■ Economical ecoefficiency mode

Technical data

Order Number		1.169-904.0
EAN code		4054278167206
Current type	Ph / V / Hz	1 / 240 / 50
Flow rate	l/h	240-560
Pressure	bar / MPa	30-120 / 3-12
Max. temperature	°C	80 / 155
Power rating	kW	3
Consumption fuel oil	kg/h	3,5
Fuel tank	l	15
Weight	kg	107,4
Dimensions (L x W x H)	mm	1060 × 650 × 920

Equipment

Trigger gun		EASY!Force Advanced
High-pressure hose	m	10 / ID 6, 250 bar
Spray lance	mm	1050
Power nozzle		■
SDS system		■
ANTI!Twist		■
Pressure switch control		■
Integral fuel and detergent tank		■
Servo Control		-

■ Included in delivery.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0


KÄRCHER


		Order Number	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sides								
High-pressure hose, 10 m DN 8, AVS trigger gun connector	1	6.110-031.0	ID 8	315 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 15 m DN 8, AVS trigger gun connector	2	6.110-030.0	ID 8	315 bar	15 m		15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 20 m DN 8, AVS trigger gun connector	3	6.110-032.0	ID 8	315 bar	20 m		20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	▲
High-pressure hose, 30 m DN 8, including rotary coupling	4	6.110-014.0	ID 8	315 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose, 15 m DN 10, 220 bar, extension	5	6.110-042.0	ID 10	220 bar	15 m		15 m high-pressure hose M 22 x 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	▲
High-pressure hose, 20 m DN 10, 220 bar, extension	6	6.110-043.0	ID 10	220 bar	20 m		with union on both sides, M 22 x 1.5 with anti-kink protection. NW 10/155°C/220 bar	▲
High-pressure hose, 25 m DN 10, extension, not rotatable	7	6.110-044.0	ID 10	220 bar	25 m			▲
Hose assembly premium DN10 22MPa 40m	8	6.110-045.0	ID 10	220 bar	40 m			▲
Hose assembly premium DN12 21MPa 15m	9	6.110-059.0	ID 12	210 bar	15 m		High-pressure hose for water volumes greater than 1,800 l/h. With union on both sides. 2x M 22 x 1.5 with anti-kink protection.	▲
Hose assembly premium DN12 21MPa 40m	10	6.110-060.0	ID 12	210 bar	40 m			▲
Hose assembly TR DN10 22MPa 10m	11	6.110-041.0	ID 10	220 bar	10 m			▲
High-pressure hose, 10 m DN 6, AVS trigger gun connector	12	6.110-035.0	ID 6	250 bar	10 m		10 m high-pressure hose (M 22 x 1.5) with kink protection.	■
	13	6.110-034.0	ID 6	250 bar	10 m		With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	□
High-pressure hose, 10 m, DN 6, 300 bar, AVS trigger gun connection	14	6.110-056.0	ID 6	300 bar	10 m		With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□
Longlife 400 with unions on both sides								
High-pressure hose Longlife 400, 30 m DN 8, including rotary coupling	15	6.110-023.0	ID 8	400 bar	30 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 20 m, DN 8, extension	16	6.110-027.0	ID 8	400 bar	20 m		with rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose Longlife 400, 15 m, DN 8, including rotary coupling	17	6.110-029.0	ID 8	400 bar	15 m		With rotary coupling, 2 x M 22 x 1.5	▲
High-pressure hose 1.5 m, DN 8, including connectors	18	6.110-024.0	ID 8	400 bar	1.5 m		1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
	19	6.110-069.0	ID 8	400 bar	1.5 m			□
High-pressure hose packaged	20	6.110-038.0	ID 8	400 bar	10 m			□
Food industry version with unions on both sides								
High-pressure hose, 10 m ID 8, suitable for food industry, extension piece	21	6.110-051.0	ID 8	250 bar	10 m		10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0



		Order Number	ID	Max. working pressure	Length		Price	Description	
High-pressure hose, 20 m ID 8, suitable for food industry, extension piece	22	6.110-052.0	ID 8	250 bar	20 m			20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲
High-pressure hose 15 m ID 6, AVS trigger gun connector 11 mm, suitable for food industry, grey	23	6.110-063.0	ID 6	250 bar	15 m			15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	□
Longlife food industry version with unions on both sides									
High pressure hose food DN 8 / 10 m	24	6.110-053.0	ID 8	400 bar	10 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	▲
High-pressure hose Longlife 400, 15 m, ID 6, AVS trigger gun connection	25	6.110-054.0	ID 8	400 bar	20 m			Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0



		Order Number	Flow rate				Price	Description	
Trigger guns									
Extended easy press trigger gun	1	4.118-005.0						Extended easy press high-pressure trigger gun for high-pressure hoses with rotating connector.	■
Servo Control									
Servo control	2	4.118-007.0	0-750 l/h					Servo control for water flow and pressure control (< 750 l/h) on trigger gun.	□
Quick connect									
Quick-fitting pipe union coupler trapezo	3	2.115-000.0							□
Quick-fitting pipe union plug nipple tra	4	2.115-001.0							□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0



1-4

		Order Number	Nozzle size				Price	Description	
Power nozzle spray angle 25°									
Power nozzle, spray angle 25°	1	2.113-007.0	42						■
HP nozzle spray angle 0°									
High-pressure nozzle spray angle 0°	2	2.113-033.0	45					High-pressure nozzle with powerful jet for extremely stubborn dirt.	□
Power nozzle spray angle 15°									
Power nozzle spray angle 15°	3	2.113-046.0	45					Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	□
Power nozzle spray angle 40°									
Power nozzle spray angle 40°	4	2.113-053.0	45					Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER


		Order Number	Max. working pressure	Length			Price	Description	
Rotating spray lances									
1050 mm lance, rotatable, ergonomic	1	4.112-000.0	300 bar	1050 mm				1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
Lance 250 mm, non-rotatable	2	4.112-027.0	300 bar	250 mm					□
550 mm lance, non-rotatable	3	4.112-024.0	300 bar	400 mm					□
Rotatable lance, 600 mm, ergonomic	4	4.112-007.0	300 bar	600 mm				600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Lance 850 mm, rotatable, ergonomic	5	4.112-006.0	300 bar	840 mm				850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Lance 1550 mm, rotatable, ergonomic	6	4.112-018.0	300 bar	1550 mm				1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Lance 2050 mm, rotatable, ergonomic	7	4.112-021.0	300 bar	2050 mm				2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
Jet pipe extension TR 1000 mm	8	4.112-048.0	300 bar	1000 mm					□
Double lance									
Double lance 960 mm	9	2.112-016.0	310 bar	960 mm				960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	□
Angular spray lance									
WC and gutter lance	10	4.112-029.0						Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
Flexible spray lance									
Flexible lance 1050 mm	11	4.112-035.0	210 bar	1050 mm				1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	□
Articulated joint TR 20	12	4.112-057.0	300 bar						□
Telescopic spray lance									
Telescopic jet pipe	13	4.112-037.0	225 bar	5400 mm					□
Restraint belt for telescopic jet pipe	14	6.373-987.0						Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible.	□
Gutter cleaner									
Gutter cleaning lance	15	2.112-015.0		960 mm				The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	□
Undercarriage spray lance									
Underbody lance	16	4.112-032.0		700 mm				Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	□
Additional handle									
	17	4.321-380.0							□
Weed control									
WR 50 trapezoidal thread	18	2.114-013.0							□
WR 20 trapezoidal thread	19	2.114-014.0							□
WR 100	20	2.114-015.0							□
WR 10	21	2.114-016.0							□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0




		Order Number					Price	Description	
Crane lifting kit									
Add-on kit suspension crane HDS C	1	2.642-638.0							☐
Flame monitoring attachment kit									
ABS flame monitor for HDS C	2	2.642-711.0							☐
Y distributor									
Y distributor	3	4.111-024.0							☐

■ Included in delivery.
 □ Available accessories.
 ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER


		Order Number	Flow rate	Nozzle size	Diameter	Price	Description	
Hard Surface Cleaner FRV 30								
Add-on kit hose attachment	1	2.642-528.0						☐
Add-on kit dirt trap	2	2.642-532.0						☐
Hard surface cleaner FR 30 ME								
FR 30 ME surface cleaner	3	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	☐
Machine-specific nozzle kit for FR								
Nozzle kit for surface cleaners (type-specific) 500 - 650 l/h	4	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	☐
Machine-specific nozzle kits for FRV								
Nozzle kit 045 for FRV 30	5	2.642-432.0		45				☐
Hard surface cleaner FRV 30 Me								
Suction hose FRV 30 me	6	4.441-040.0						☐
FRV 30 ME	7	2.111-012.0					Surface cleaner with integrated waste water pick-up	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER


		Order Number						Price	Description	
Nozzle union										
Protection part TR only for replacement	1	4.112-011.0								☐
Spacer (including nozzle union)										
Spacer (incl.nozzle union)	2	5.394-294.0							Guarantees constant safety clearance, e.g. for tyres and bodywork. Helps prevent damage to sensitive surfaces. Mounts directly to lance.	☐
Rotary coupling										
Rotary coupling	3	4.111-021.0							Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector M 22 x 1.5 m. With grip protection.	☐
Coupling										
Coupler -2xM22x1,5	4	4.111-037.0							Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	☐
Connector										
Nozzle connector/screw connector	5	4.111-022.0							Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	☐
	6	4.111-038.0								☐
Adapter EASY!Lock										
Adapter 1 M22AG-TR22AG	7	4.111-029.0								☐
Adapter 2 M22IG-TR22AG	8	4.111-030.0								☐
Adapter 3 M22IG-TR22AG	9	4.111-031.0								☐
Adapter M22 - Swivel	10	4.111-032.0								☐
Adapter 5 TR22IG-M22AG	11	4.111-033.0							M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	☐
Adapter 6 TR22IG-M22AG	12	4.111-034.0								☐
Adapter 7 M18IG-TR20AG	13	4.111-035.0								☐
Adapter 8 TR20IG-M18AG	14	4.111-036.0								☐
ADAPTER for replacement TR22IG-M22AG Er	15	4.111-046.0								☐
Flue pipe										
Flue gas adapter	16	4.656-149.0							Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for connection to a stack system).	☐
	17	4.656-080.0								☐
HP detergent injector										
Detergent injector for high and low pressure (without nozzles)	18	4.637-032.0							Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	☐
Detergent injector for high pressure	19	4.637-033.0							Cleaning agent dosage at high pressure 3 - 5 %	☐
Machine-specific nozzle kit with order no. 3.637-170										
Nozzle insert trapezoidal thread HDS-GER	20	4.769-009.0								☐
Nozzle insert with order no. 3.637-001										
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	21	4.769-003.0							Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0




		Order Number					Price	Description	
Low pressure for units rated up to 1100 l/h	22	4.769-001.0						For low pressure with machines up to 1.100 l/h	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0


KÄRCHER


		Order Number	Max. working pressure	Nozzle size	Diameter	Price	Description	
Barrel and tank cleaning								
Barrel cleaner BC 14/12	1	2.112-020.0					The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums - in particular oak barrels with a capacity between 225 and 600 liters.	☐
Pipe cleaning hose, ID 6								
Hose assembly TR pipe cleaning DN6 max.2	2	6.110-046.0	250 bar					☐
Pipe cleaning hose, DN 6, 20 m, 220 bar	3	6.110-008.0	250 bar				20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	☐
Hose assembly TR pipe cleaning DN6 max.2	4	6.110-047.0	250 bar					☐
Pipe cleaning nozzle								
Dirt blaster pipe cleaning D21/040	5	4.765-001.0		40	21 mm			☐
Dirt blaster pipe cleaning D30/040	6	4.765-004.0		40	30 mm			☐
Nozzle pipe cleaning size 120	7	5.763-089.0		120	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	☐
Pipe cleaning nozzle	8	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	☐
	9	5.763-016.0		60	16 mm			☐
	10	5.763-017.0		50	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	☐
Rotating pipe cleaning nozzle	11	6.415-428.0		50	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	☐
Drain cleaning dirt blaster D 25/040	12	6.415-944.0		40	25 mm		The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	☐
Drain cleaning dirt blaster D 30/040	13	6.415-946.0		40	30 mm			☐
Drain cleaning dirt blaster D 35/040	14	6.415-948.0		40	35 mm			☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0



		Order Number	Max. working pressure	Nozzle size			Price	Description	
Angle vario nozzle 0°-90°									
Variable angle nozzle 0-90°	1	4.113-006.0		80				Variable angle nozzle for spray angle adjustment from 0° to 90°. For easy adjustment to all kinds of soiling and surfaces.	☐
Dirt blaster, large									
Dirt blaster - without changeover function	2	4.114-027.0	300 bar	50				The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER



		Order Number	Nozzle size				Price	Description	
Wet blasting attachment (without nozzle)									
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	☐
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	☐
Nozzle pack for wet blasting attachment									
Nozzle pack TR wet jet set 0045	3	2.112-022.0	45						☐
Boron carbide nozzle									
Boron carbide nozzle, for machines as of 1000 l/h	4	6.415-084.0	6 mm					In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER



		Order Number	Flow rate					Price	Description	
Cup foam lance										
Foam lance TR	1	4.112-053.0	350-600 l/h							☐
Packing complete for 6.394-969.0	2	2.112-018.0								☐
Tank grey only for replacement 1L	3	6.414-050.0								☐
Inno Foam Set										
Inno foam kit with detergent injector	4	2.112-000.0							High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	☐
Inno foam kit	5	2.112-008.0								☐
Easy Foam Set										
Easy Foam Set with RM injector	6	2.112-010.0							HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	☐
Easy foam set	7	2.112-011.0								☐
Nozzle kits for Inno/Easy Foam Set										
Nozzle kit 060 for Inno/Easy Set 600 - 700 l/h	8	2.111-018.0	600-700 l/h						Optimal adaptation to different machine outputs for economic use.	☐
Foam nozzle mounting kit										
Foam nozzle kit	9	2.112-013.0							Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER


		Order Number	Length					Price	Description	
Hose reel add-on kit										
Hose reel kit, plastic, for HDS 5/12 C - HDS 8/18-4 C	1	2.110-010.0	20 m							☐
Automatic, self-winding hose reels										
Add-on kit hose reel plastics	2	6.392-074.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Add-on kit hose reel	3	6.392-083.0	20 m						Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
Hose reel, automatic, 20 m, painted	4	6.392-106.0	20 m						Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
	5	6.392-105.0	20 m							☐
Hose reel, automatic, 20 m, stainless steel	6	6.392-076.0	20 m						Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐
ABS hose reel stainless steel	7	6.392-122.0	20 m						High-grade, automatic steel hose reel. Especially suitable for use in the food industry. The material and finish provide for a corrosion-resistant, watertight capsuled sprong drive. Connection for HP hoses with nipple.	☐
Add-on kit hose reel TR 40m	8	6.392-442.0	40 m							☐
Swivel holder	9	2.639-931.0							Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	☐
ABS wall fastening stainless steel	10	2.641-867.0							Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	☐
Anbausatz Schlauchtrommel automatik										
Add-on kit automatic hose reel HDS-C	11	2.110-012.0								☐
Add-on kit hose reel	12	2.110-013.0								☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0



		Order Number	Flow rate				Price	Description	
Push-on washing brush									
Push-on wash brush, M 18 x 1.5	1	4.113-001.0						Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 x 1.6.	☐
Rotating washing brush									
	2	4.113-004.0	500-800 l/h						☐
	3	4.113-003.0	500-800 l/h						☐

■ Included in delivery.
 ☐ Available accessories.
 ▲ Extension hose.

ACCESSORIES FOR HDS 6/12 C

1.169-904.0

KÄRCHER


		Order Number	Length	Diameter		Price	Description	
Geka coupling								
With hose nozzle, R 1/2"	1	6.388-461.0					with hose liner	☐
With hose nozzle, R 3/4"	2	6.388-455.0						☐
With hose nozzle, R 1"	3	6.388-465.0						☐
Hose coupling	4	6.388-458.0					with female thread	☐
Suction filter								
Water filter	5	6.414-956.0						☐
Suction filter with check valve	6	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	☐
Fine-mesh water filter								
Fine-mesh water filter with adapter	7	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	☐
Fine-mesh water filter, 100 µm, R 1"	8	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	☐
Water supply hose								
Water supply hose	9	4.440-038.0	7,5 m				NW 13 R1" / R 3/4", up to 30 °C	☐
	10	4.440-207.0	7,5 m				NW 19 R1" / R 3/4", up to 85 °C, for pick-up	☐

■ Included in delivery. □ Available accessories. ▲ Extension hose.