

High pressure cleaner

Cold water, mobile - series 4x4 KD1840























Туре		KD1840-Premium
Voltage	3/400-415V/ 50Hz	► Hose-Reel
Operating pressure	30-120bar/ 3-12MPa	 15m HP-Hose DN10 - 315bar Trigger-Gun with swivel Spray-Lance 900mm c/w Nozzle- Protection Stainless-Steel Jet-Nozzle 25° Spray-Lance 900mm c/w Rotary-Nozzle 17l Water-Storage tank Water-Supply separation acc. water reg. Chemical supply in high-pressure Jet c/w Metering-valve
Max. pressure	140bar/ 14MPa	
Discharge capacity	300 - 1.800l/h	
Nozzle size	150	
Max. Inlet temperature	45°C	
Pump speed	1400rpm	
Connected load	7,4kW / 13,1A	
Electrical protection	3x16A slow-blowing	
Weight net / with package		105 kg / 129 kg
Dimensions device / with package (LxWxH)		1020 x 620 x 1000 mm / 1050 x 760 x 1180 mm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, robust rotary on-off switch, 7,5m connection cable, removable ergonomic drawbar