## High Pressure Cleaner

EFIFLE®

The better way to clean

Hot water, mobile - Series HDE HDE840 12 kW





















Туре		HDE840 12kW-Standard	HDE840 12kW-Premium
Voltage	3/ 400-415V/ 50Hz	<ul> <li>Etronic II - Controls</li> <li>10m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle- Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>	<ul> <li>Etronic II - Controls</li> <li>Hose-Reel</li> <li>20m HP-Hose DN08 - 315bar</li> <li>Trigger-Gun with swivel</li> <li>Spray-Lance 900mm c/w Nozzle- Protection</li> <li>Stainless-Steel Jet-Nozzle 25°</li> <li>Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>Water-Supply separation acc. water reg.</li> <li>Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-130bar/ 3-13MPa		
Max. pressure	150bar/ 15MPa		
Discharge capacity	300 - 720l/h		
Nozzle size	045		
Heating capacity	12kW		
Hot water capacity	30 - 80°C		
Pump speed	1400rpm		
Connected load	16,8kW / 26,2A		
Electrical protection	3x32A slow-blowing		
Weight net / with package		119 kg / 140 kg	128 kg / 149 kg
Dimensions device / with package (LxWxH)		1070 x 735 x 785 mm / 1160 x 770 x 960 mm	1070 x 735 x 1310 mm / 1160 x 770 x 1350 mm

Robust, corrosion-resistant, self-supporting device chassis, impact-resistant device-cover made of ABS, stainless-steel hotwater-boiler with 65l capacity with pre-heating and buffer storage for immediate hot-water use and hot-water preparation during stand-by operation, triplex-piston pump with chrome nickel pump head (hot-water resistant), high-performance ceramic piston, stainless-steel valves, leakage-return, Etronic II - controls: (start-stop system with switch-off delay, stand-by system for heating, low-water cut-off), unloader safety-valve c/w Infinitely variable pressure and quantity regulation, 4 large rubber wheels for rough terrain, with a patented wheel brake 2-way, storage possibility for all accessories, 2 integrated detergent-tank with 20l capacity, 2-stage rotary on-off switch with stand-by function, 7,5m connection cable, removable ergonomic drawbar