



HIGH-PRESSURE WASHERS - HOT WATER

# PW-H50 PLUS\*

PRESSURE

100÷200  
bar

FLOW RATE

600÷1000  
l/h

ABSORBED POWER

3÷6,4  
kW

### EXCLUSIVE CHARACTERISTICS

- ▶ DELAYED TOTAL STOP - DTS
- ▶ INTELLIGENT AUTOMATIC SWITCH OFF - IASF
- ▶ MICRO LEAKAGE CONTROL - MLC
- ▶ DRY RUNNING PROTECTION - DRP
- ▶ NOZZLE CLOGGED CONTROL - NCC
- ▶ BOILER IGNITION DELAY - IBD
- ▶ WORKING HOURS COUNTER - WHC
- ▶ ELECTRONIC TEMPERATURE STABILIZER CONTROL - ETSC
- ▶ LIMESCALE/CORROSION PROTECTION UNIT - LCPU
- ▶ ANTI-SCALE LEVEL CONTROL - ALC
- ▶ FUEL LEVEL CONTROL - FLC
- ▶ MAINTENANCE CHECK LED - MCL



PW-H50 PLUS



PW-H50/4 PLUS

\* PLUS VERSION

### MOST FREQUENTLY USE



### INNOVATIONS



G6000™ CERAMIC TECH GUN



MSC™ MULTIFUNCTION SAFETY CONTROL



ETC™ ELECTRONIC TEMPERATURE CONTROL



M421 ANTI-SCALE

### SPECS



CONTROL PANEL WITH INDICATORS LAMPS



ERGONOMIC HANDLE PROVIDED WITH LANCE HOLDER FOR AN EASY TRANSPORT



ACCESSORIES STORAGE COMPARTMENT

## TECHNICAL DATA

### DELAYED TOTAL STOP VERSION

		<b>PW-H50P D1310P4 M</b>	<b>PW-H50P D1012P4 M</b>	<b>PW-H50P D1813P4 T</b>	<b>PW-H50P D1915P4 T</b>	<b>PW-H50P D2017P4 T</b>
<b>3 WHEELS</b>						
Code		IDAC40873	IDAC40874	IDAC40875	IDAC40876	IDAC40877
<b>4 WHEELS</b>						
Code		IDAC40883	IDAC40884	IDAC40885	IDAC40886	IDAC40887
<b>PERFORMANCE</b>						
Operating pressure	bar/Mpa	30-130/3-13	30-100/3-10	30-180/3-18	30-190/3-19	30-200/3-20
Flow rate	l/h	300-600	360-720	450-800	450-900	500-1000
Outlet water temperature	°C	30-140	30-140	30-140	30-140	3-140
Power supply	Ph-V-Hz/A	1-230-50/13,8	1-230-50/14	3-400-50/9,7	3-400-50/10,6	3-400-50/13,2
Absorbed power	kW	3,1	3,2	5	5	6,4
Motor pole/rpm		4-1400	4-1400	4-1400	4-1400	4-1400
Remote control		DTS	DTS	DTS	DTS	DTS
Pump/head/pistons		lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic	lpc plunger/brass/ ceramic
Boiler thermal power	kW	40	55	70	70	≥70
Fuel consumption	kg/h	3,2	5,8	5,8	5,8	5,8
Fuel tank	l	25	25	25	25	25
Detergent tank	l	22	22	22	22	22
Detergent delivery		high pressure	high pressure	high pressure	high pressure	high pressure
Dimension (LxWxH)	cm	110x70x70	110x70x70	110x70x70	110x70x70	110x70x70
Weight	kg	107	109	120	122	140

## STANDARD EQUIPMENT

CODE: IPPR40020  
HANDGRIP G6000



CODE: LCPR40087  
EXTENSION P70 - INOX



CODE: UGLN49986  
H.P. NOZZLE 1/4 UG.1504  
(FOR 1310/1813)



CODE: UGLN05200  
H.P. NOZZLE 1/4 UG.1505  
(FOR 1012)



CODE: UGLN49987  
H.P. NOZZLE 1/4 UG.15045  
(FOR 1915/2017)



CODE: TBAP25324  
HIGH PRESSURE HOSE  
10 m



## OPTIONAL ACCESSORIES

CODE: SPID24911  
ROTATING HYDROBRUSH  
LANCE P70



CODE: SPID24939  
FIXED HYDROBRUSH  
LANCE P70



CODE: LCLC41140  
LANCE FOR WASHING  
FLOORS INOX



CODE: LCLC49492  
LANCE FOR WASHING FLOORS  
Ø 0,35 (FOR 1310/1915)



CODE: LCLC49494  
LANCE FOR WASHING  
FLOORS Ø 0,55 (FOR 1012)



CODE: LCLC49493  
LANCE FOR WASHING FLOORS  
Ø 0,45 (FOR 1813/2017)



CODE: KTRI40235  
HOSE REEL KIT



CODE: RCIN10810  
HOSE COUPLING M22



CODE: KTRI29377  
FEEDING KIT



CODE: TBAP23853  
DRAIN KIT 10 m



CODE: KTRI29366  
PLUNGER EJECTOR DEVICE



CODE: LCPR40014  
TURBO LANCE M22 D.1,30  
(FOR 1310/1813)



CODE: LCPR40135  
TURBO LANCE P70 M22  
0,45 (FOR 1915)



CODE: LCPR14859  
SANDBLASTER KIT Ø 1,5 mm  
(FOR 1915/2017)



CODE: LCPR14858  
SANDBLASTER KIT Ø 1,4 mm  
(FOR 1310/1813)



CODE: LCPR13557  
SANDBLASTER KIT Ø 1,6 mm  
(FOR 1012)



CODE: PRCH00065  
SAND BAG 50 Kg



CODE: PRCH40039  
ANTI-SCALE TREATMENT  
M421 1 Kg X 6



CODE: PRCH40040  
ANTI-SCALE TREATMENT  
M421 10 Kg



CODE: KTRI40316  
MAINTENANCE KIT 500H  
(FOR 1310)



CODE: KTRI40314  
MAINTENANCE KIT 500H  
(FOR 1813/1915)

CODE: KTRI40430  
MAINTENANCE KIT 500H  
(FOR 1012)

CODE: KTRI40431  
MAINTENANCE KIT 500H  
(FOR 2017)