

High Pressure Cleaner

Cold water, mobile - Series 3x3

KD823 UK



Type	KD823 UK-Standard		KD823 UK-Premium
Voltage	1/ 240V/ 50Hz		▶ Hose-Reel
Operating pressure	30-125bar/ 3-12,5MPa		▶ 15m HP-Hose DN08 - 315bar
Max. pressure	140bar/ 14MPa		▶ Trigger-Gun with swivel
Discharge capacity	300 - 720l/h		▶ Spray-Lance 900mm c/w Nozzle-Protection
Nozzle size	050		▶ Stainless-Steel Jet-Nozzle 25°
Max. Inlet temperature	45°C		▶ Spray-Lance 900mm c/w Rotary-Nozzle
Pump speed	1400rpm		▶ 17l Water-Storage tank
Connected load	3,1kW / 12,3A		▶ Water-Supply separation acc. water reg.
Electrical protection	13A slow-blowing		▶ Chemical supply in high-pressure Jet c/w Metering-valve
Weight net / with package	46 kg / 66 kg		50 kg / 70 kg
Dimensions device / with package (LxWxH)	805 x 485 x 950 mm / 790 x 595 x 810 mm		830 x 485 x 950 mm / 790 x 595 x 810 mm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5,0m connection cable, removable ergonomic drawbar