


# High Pressure Cleaner

Cold water, mobile - Series 3x3

KD940



Type		KD940-Standard	KD940-Premium
Voltage	3/ 400-415V/ 50Hz	<ul style="list-style-type: none"> <li>▶ 10m HP-Hose DN08 - 315bar</li> <li>▶ Trigger-Gun with swivel</li> <li>▶ Spray-Lance 900mm c/w Vario-Nozzle</li> <li>▶ Stainless-Steel Jet-Nozzle 25°</li> <li>▶ 15l Cleaning-Detergent tank</li> <li>▶ Detergent-Supply c/w Low-Pressure Injector and metering-valve</li> </ul>	<ul style="list-style-type: none"> <li>▶ Hose-Reel</li> <li>▶ 15m HP-Hose DN08 - 315bar</li> <li>▶ Trigger-Gun with swivel</li> <li>▶ Spray-Lance 900mm c/w Nozzle-Protection</li> <li>▶ Stainless-Steel Jet-Nozzle 25°</li> <li>▶ Spray-Lance 900mm c/w Rotary-Nozzle</li> <li>▶ 17l Water-Storage tank</li> <li>▶ Water-Supply separation acc. water reg.</li> <li>▶ Chemical supply in high-pressure Jet c/w Metering-valve</li> </ul>
Operating pressure	30-190bar/ 3-19MPa		
Max. pressure	210bar/ 21MPa		
Discharge capacity	300 - 840l/h		
Nozzle size	045		
Max. Inlet temperature	45°C		
Pump speed	1400rpm		
Connected load	5,2kW / 9,1A		
Electrical protection	3x16A slow-blowing		
Weight net / with package		54 kg / 74 kg	58 kg / 78 kg
Dimensions device / with package (LxWxH)		805 x 485 x 950 mm / 790 x 595 x 810 mm	830 x 485 x 950 mm / 790 x 595 x 810 mm

Self-supporting, robust, rotation-moulded device-chassis, impact-resistant device-cover made of ABS, triplex-piston pump with brass pump head, nickel plated, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min, unloader safety-valve c/w infinitely variable pressure and quantity regulation, 2 large rubber wheels for rough terrain with rubber stand, storage possibility for all accessories, robust rotary on-off switch, 5.0 m connection cable, removable ergonomic drawbar