


High Pressure Cleaner

Cold water, stationary - Series KS

KS1140 - hot water resistant



Type	KS1140	KS1140-INOX
Voltage	3/400-415V/ 50Hz	
Operating pressure	30-180bar/ 3-18MPa	
Max. pressure	200bar/ 20MPa	
Discharge capacity	300 - 1000l/h	
Nozzle size	055	
Max. Inlet temperature	80°C	
Pump speed	1400rpm	
Connected load	6,5kW / 11,7A	
Electrical protection	3x16A slow-blowing	
Weight net / with package	112 kg / 126 kg	112 kg / 126 kg
Dimensions device / with package (LxWxH)	780 x 510 x 540 mm / 1200 x 800 x 700 mm	780 x 510 x 540 mm / 1200 x 800 x 700 mm
<p>Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), wall-bracket, drawtable on telescopic rails, triplex-piston pump with brass pump head, hot-water resistant up to 80°C, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min with leakage-recognition, unloader safety-valve c/w infinitely variable pressure and quantity regulation, robust rotary on-off switch, 7,5m connection cable</p>		
Art. No.	155	155000
Retail price plus VAT	3.469,00 €	4.299,00 €