


High Pressure Cleaner

Cold water, stationary - Series KS

KS823 - hot water resistant



Type	KS823		KS823-INOX
Voltage	1/ 230V / 50Hz		
Operating pressure	30-120bar/ 3-12MPa		
Max. pressure	140bar/ 14MPa		
Discharge capacity	300 - 720l/h		
Nozzle size	050		
Max. Inlet temperature	80°C		
Pump speed	1400rpm		
Connected load	2,6kW / 12,8A		
Electrical protection	16A träge		
Weight net / with package	102 kg/ 116 kg		102 kg/ 116 kg
Dimensions device / with package (LxWxH)	780 x 510 x 540 mm / 1200 x 800 x 700 mm		780 x 510 x 540 mm / 1200 x 800 x 700 mm
<p>Self-supporting, robust, device-chassis made from galvanized steel and powder-coated (option INOX: device-chassis made out of stainless-steel), wall-bracket, drawtable technic on telescopic rails, triplex-piston pump with brass pump head, hot-water resistant up to 80°C, high-performance ceramic piston, stainless-steel valves, leakage-return, start-stop system with switch-off delay, total-switch-off after 20min with leakage-recognition, unloader safety-valve c/w infinitely variable pressure and quantity regulation, robust rotary on-off switch, 7,5m connection cable</p>			
Art. No.	157		157000
Retail price plus VAT	2.569,00 €		3.399,00 €